

**GROUT / SCG** SELF CONSOLIDATING GROUT

1 OF 6

**MATERIAL SAFETY DATA SHEET**

(Complies with OSHA CFR 1910.1200 ANSI Z 400.1-1998)

Approval Date: May 11, 2011

**SECTION 1: Chemical Product and Company Identification**

**Product Name:** SPEC MIX® Self Consolidating Grout  
 SPEC MIX® Fine Self Consolidating Grout  
 SPEC MIX® Coarse Self Consolidating Grout

**Manufacturer Name and Address:** SPEC MIX® Inc.  
 2025 Centre Pointe Blvd.  
 Mendota Heights, MN 55120

**Telephone Contact Number and Hours of Operation:** (888) 773-2649; 8:00 a.m. – 4:00 p.m. Central Time

**Emergency Telephone Contact Number:** (800) 222-1222

**SECTION 2: Composition/Information on Ingredients**

<u>Hazardous Ingredients (*)</u>	<u>CAS No.</u>	<u>OSHA PEL</u> TWA	<u>ACGIH TLV</u> TWA
Portland cement	65997-15-1	15mg/m <sup>3(1)</sup> 5mg/m <sup>3(2)</sup>	0mg/m <sup>3</sup> NE
Fly Ash	68131-74-8	5mg/m <sup>3</sup>	5mg/m <sup>3</sup>
Crystalline silica (sand and gravel)	14808-60-7	see 29 CFR 1910.1000 table z-3 0.05 mg/m <sup>3(3)</sup>	
Calcium sulfate	7778-18-9	15mg/m <sup>3(1)</sup> 5mg/m <sup>3(2)</sup>	10mg/m <sup>3</sup>

- 1 - PNOC (Particulate not otherwise classified) as total dust
- 2 - PNOC as respirable fraction
- 3 - As respirable fraction
- 4 - Chromium (III) compounds as chromium

**\*All ingredients in quantities > 1.0% (0.1% for carcinogens) that are potentially hazardous per OSHA definitions**

**NDA = no data available NE = not established**

**Some states enforce the PELs that OSHA promulgated in 1989, which were subsequently vacated by the U.S. Supreme Court. Check with your state OSHA agency to determine which PEL is enforced in your jurisdiction.**

**GROUT / SCG** SELF CONSOLIDATING GROUT

2 OF 6

**SECTION 3: Hazards Identification**      **EMERGENCY OVERVIEW****Physical Description:** Natural gray solid**Odor:** None / Characteristic**Additional hazard information for humans and the environment:** Dust may form explosive mixture in air, dust may cause eye irritation & wet materials on floor presents a slipping hazard

**Potential Health Effects: Warning!** Contact with wet mortar can burn eyes and skin. Permanent eye damage can result from eye contact. Dust from the dry material can cause severe irritation and possibly burns to the eyes and respiratory tract with coughing and nasal discharge. Lung damage and possibly pulmonary edema can result from dust exposure. Skin contact may not cause an immediate burning sensation. It is important to begin skin first-aid even if there is no immediate burning sensation. Repeated or prolonged skin contact may cause skin allergic reactions. Personnel responding to a spill of this material should wear appropriate personal protective equipment.

<b>Fire Hazards:</b>	<b>NFPA Ratings:</b>	Health = 2	Fire = 0	Reactivity = 0	Special = NDA
	<b>HMIS Ratings:</b>	Health = 2	Fire = 0	Reactivity = 0	Protective Equipment = X

**SECTION 4: First Aid Measures**

**Note:** Signs and symptoms of skin burns may be delayed. Begin first aid immediately following skin contact even if there is no immediate burning sensation.

**Eye Contact:** Hold eye open and rinse slowly and gently with water for 30 minutes. Remove any contact lenses (if easy to do), after the first 5 minutes then continue rinsing the eye. Get medical attention immediately.

**Skin Contact:** Flush affected area for 20 minutes then wash affected area with mild soap and water. Get medical attention immediately.

**Ingestion:** Get medical attention immediately. Immediately rinse mouth with plenty of water. Have person sip a glass of water if able to swallow — **NEVER** give anything by mouth to an unconscious person. Do not induce vomiting.

**Inhalation:** Remove to fresh air. Seek medical attention immediately if breathing becomes difficult.

**SECTION 5: Fire Fighting Measures**

**Extinguishing Media:** Noncombustible. Use media suitable for surrounding fire. / Use water spray or CO<sub>2</sub>

**Flashpoint:** NDA

**Hazardous Products of Combustion:** Calcium oxide fumes & Oxides of carbon and sulfur

**Auto Ignition Temperature:** NDA

**Flammable Limits:** LEL;NDA UEL; NDA / None

**Unusual Fire and Explosion Hazards:** None known.

**Protective Equipment:** Use NIOSH/MSHA approved SCBA and bunker gear.

**SECTION 6: Accidental Release Measures**

Do not attempt to clean up chemical spills without appropriate personal protective equipment (see section 8). For a spill of the dry material, use a HEPA (high efficiency particle air) vacuum to collect material and place in seal able containers for disposal. For a wet spill, absorb or cover with dry earth, sand or other noncombustible material and transfer to containers for disposal. Neutralize spill area. Use materials that can withstand the potentially corrosive nature of this product. Do not get water inside containers. See Disposal Comments in Section 13.

# GROUT / SCG SELF CONSOLIDATING GROUT

3 OF 6

## **SECTION 7: Handling and Storing**

**Handling:** Avoid contact with eyes and skin. Avoid generating and breathing dusts. Dust may be generated from cutting, grinding, drilling, sawing, or otherwise disturbing hardened concrete. Use with proper personal protective equipment (see Section 8).

**Storage:** Store upright in a cool, dry, well-ventilated area out of direct sunlight. Protect containers from physical damage. Do not roll containers. Keep containers tightly closed at all times. Do not reuse container. Store away from incompatible materials (see Section 10). Keep out of reach of children.

## **SECTION 8: Exposure Controls and Personal Protective Equipment**

**Engineering Controls:** If industrial hygiene surveys show that exposures exceed TLVs or other exposure limits, use a combination of local exhaust and general dilution/ventilation to control exposures. If that is not feasible, see recommendations under "Respiratory Protection."

**Skin:** Wear safety glasses with side shields and goggles or face shield. Wear impermeable gloves and protective clothing.

**Respiratory Protection:** NIOSH approved N-95 cartridge respiratory protection is necessary if any of the standards in Section 2 are exceeded. Seek professional advice prior to respirator selection or use. Follow OSHA respirator regulations (29 CFR 1910.134). Use a positive pressure air supplied respirator if there is a potential for an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection

**Safety Equipment:** Eyewash and deluge shower.

## **SECTION 9: Physical and Chemical Parameters**

**Physical State:** Solid

**Odor:** None / Characteristic

**Vapor Density (air = 1):** NDA

**Percent Volatile By Volume:** NDA

**Melting Point:** NDA

**Viscosity:** NDA

**Bulk Density:** NDA

**PH:** NDA

**Appearance:** Natural gray or colored

**Vapor Pressure:** NDA

**Evaporation Rate (n-butyl acetate = 1):** NDA

**Freezing Point:** NDA

**Boiling Point:** NDA

**Specific Gravity:** NDA

**Solubility:** Slightly soluble in water

## **SECTION 10: Stability and Reactivity**

**Stability:** Stable

**Incompatible Materials and Conditions to Avoid:** Avoid strong acids. Silica will dissolve in hydrofluoric acid and produce a corrosive gas silicone tetra fluoride. Contact with oxidizing agents such as fluorine, chlorine tetra fluoride, manganese trioxide, and oxygen difluoride may cause fires. Calcium hydroxide has been reported to undergo violent reactions with malic anhydride, nitroethane, nitromethane, nitroparaffins, nitropropane, and phosphors.

**Hazardous polymerization:** Not expected.

**Hazardous decomposition products:** Oxides of calcium & Carbon Monoxide, sulfur oxides and nitrous gases.

**GROUT / SCG** SELF CONSOLIDATING GROUT

4 OF 6

**SECTION 11: Toxicological Information**

Product Based Information: There are limited toxicological data available for this product. Exposure and occur to the dry product, the wetted product, or to dusts when hardened mortar is ground, cut, drilled, sanded or otherwise disturbed. Routes of exposure include inhalation, eye and skin contact, and ingestion. Inhalation of the dusts of the dry product or from the disturbed hardened product can cause respiratory tract irritation with coughing and nasal discharge. Shortness of breath and reduced pulmonary function may also result from inhalation. Alveolar damage and pulmonary edema resulted in animal studies from exposure to the dry product.

This product contains crystalline silica. Prolonged overexposure to quartz or crystalline silica dust can cause pneumoconiosis, silicosis (a permanent fibrotic lung disease) and potentially lung cancer. Dust can cause inflammation of the lining tissue in the nose and inflammation of the cornea. Eye contact with the wet or dry product can cause burns and permanent damage to the eyes. Skin contact with the wet product can cause burns (corrosive). Repeated or prolonged skin contact with the wet product can cause drying of the skin, dermatitis and possibly allergic skin reactions. Skin contact with the dry product can cause irritation and possibly burns. Ingestion of either the wet or dry product is expected to cause severe irritation and likely burns to the mouth, throat, esophagus, and possibly the stomach. Nausea, vomiting and diarrhea may also occur. There were no data located addressing potential reproductive, developmental, or mutagenic effects following exposure to this product.

**Ingredient Based Information:**

This product contains Portland cement (CAS# 65995-15-1). Portland cement essentially contains five compounds:

3CaO•SiO <sub>2</sub>	Tricalcium Silicate	CAS #12168-85-3
2CaO•SiO <sub>2</sub>	Dicalcium Silicate	CAS #10034-77-2
3CaO•Al <sub>2</sub> O <sub>3</sub>	Tricalcium Aluminate	CAS #12042-78-3
4CaO•Al <sub>2</sub> O <sub>3</sub> •Fe <sub>2</sub> O <sub>3</sub>	Tetracalcium Aluminoferrite	CAS #12068-35-8
CaSO <sub>4</sub> •2H <sub>2</sub> O	Calcium Sulfate Dihydrate (Gypsum)	CAS #778-18-9(# 13397-24-5)

The Portland cement may contain trace quantities (<0.05%) amounts of chromium salts or compounds (including hexavalent chromium) or other metals (including nickel compounds). Other trace constituents may include potassium and/or sodium sulfate compounds. Exposure can occur by eye or skin contact, inhalation, or ingestion. Eye contact can cause irritation. Portland cement is considered a primary skin irritant. Repeated or prolonged skin contact can cause dermatitis. Skin sensitivity may occur if hexavalent chromium is present. Inhalation of dusts may cause dyspnea based on a cross sectional study of 2736 Portland cement workers and 755 controls. In this study, 5.4% of the cement workers had dyspnea v.s. 2.7% of the controls. Ingestion can cause irritation to the mouth, throat, esophagus and stomach with nausea, vomiting and diarrhea. Data located were inconclusive regarding the association between occupational exposure to Portland cement and various cancers (e.g., stomach and lung). No data were located addressing potential reproductive or developmental affects following occupational exposure. Portland cement contains calcium sulfate (CAS# 7778-18-9). Calcium sulfate, when added to water may exist in more hydrated forms. Exposure to calcium sulfate can occur by inhalation, ingestion and eye and skin contact. Inhalation of calcium sulfate dust causes upper respiratory tract irritation primarily as a nuisance dust. Data from human occupational exposures indicate that calcium sulfate caused no lung disease in calcium sulfate miners. Ingestion may result in abdominal pain, vomiting or diarrhea. Ingestion of large amounts could cause obstruction of the gut in the pyloric region. Skin contact with calcium sulfate is not expected to cause irritation. However, skin contact with more hydrated forms of calcium sulfate may cause thermal burns during the hardening process. Eye contact with calcium sulfate may result in mechanical irritation. No adverse affects were reported after application of calcium sulfate to rabbit eyes. Calcium sulfate dihydrate was shown to cause carcinogenic effects in one study. There were no additional data located regarding the potential carcinogenic, reproductive or developmental effects following exposure to calcium sulfate.

This product may contain fly ash, which is a by-product of coal combustion. Depending on the coal source, the material may contain complex dicalciumsilicate, aluminosilicate glass, mullite, hematite, magnetite spinel and quartz. The proportion of quartz (crystalline silica) in the fly ash varies depending on the quartz content of the coal. Class C fly ash may contain free CaO as well as tricalcium aluminate and aluminosilicate glass.

**GROUT / SCG** SELF CONSOLIDATING GROUT

5 of 6

This product contains crystalline silica (CAS# 14808-60-7). Silica (crystalline) is composed of colorless crystals. Inhalation of crystalline silica is the most significant route of exposure. Inhalation of crystalline silica can lead to silicosis. Silicosis is a disabling, progressive and sometimes fatal lung disease that is characterized by the presence of typical nodulation of the lungs leading to fibrosis. Inhalation of high concentrations of crystalline silica over a short period of time (as little as a few weeks) can cause acute silicosis. Signs and symptoms of acute silicosis include progressive tiredness, fever, weight loss, cough and shortness of breath, wheezing, changes in the chest x-ray, and nonspecific chest illness. In acute silicosis, the lungs show a diffuse ground-glass appearance similar to pulmonary edema and lacking in the nodular pattern in the lungs. Chronic inhalation of lower concentrations can result in silicosis that develops and lasts over many months or years. Those with existing respiratory or lung problems may be at an increased risk from exposure. Clinical signs and symptoms of silicosis generally progress with continued exposure, advancing age, and continued smoking habits. Clinical signs and symptoms of silicosis include cough, tiredness, wheezing, and nonspecific chest illnesses. Symptoms may continue to worsen even after exposure is stopped. The risk of onset of silicosis and the progression to pulmonary lesions is related to the dust concentrations and duration of exposure. Silicosis predisposes to active tuberculosis with the combined diseases progressing more rapidly than silicosis alone. The crystalline silica that remains in the lungs can also cause emphysema, obstructive airway disease and lymph node fibrosis in humans. Occupational exposure to crystalline silica has been associated with lung cancer in some studies. Exposure to crystalline silica dust has also been associated with progressive systemic sclerosis (scleroderma) and may cause perturbations in the immune system based on human data and animal studies. Crystalline silica has been shown to inhibit human leukocyte elastase in *in vitro* studies. This may result in a decrease in bactericidal activity and set the stage for opportunistic infections. IARC has determined that crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC group 1). The National Toxicology Program considers crystalline silica a known human carcinogen. There are no data located addressing reproductive or developmental hazards of silica (crystalline) exposure.

**Possible target organs:** All tissues (possibly corrosive) and respiratory system (e.g., lungs).

**Medical conditions that may be aggravated by exposure:** Skin (e.g., sensitive skin) and respiratory or lung disorders (e.g., asthma, bronchitis).

**Carcinogens:** IARC has determined that crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC group 1). The National Toxicology Program (NTP) considers crystalline silica of a respirable size a known human carcinogen.

**SECTION 12: Ecological Information**

**Ecotoxicity:** NDA

**Environmental Fate:** NDA

**SECTION 13: Disposal Considerations**

This material (as packaged) may be considered a hazardous waste. Be aware that the waste owner has responsibility of final disposal. Regulations may also apply to empty containers, liners or rinsate. Laws may be changed or be reinterpreted; state and local regulations may be different from federal regulations. This information applies to materials as manufactured; contamination or processing may change waste characteristics and requirements.

**SECTION 14: Transport Information**

DOT Hazard Description: ND

**GROUT / SCG SELF CONSOLIDATING GROUT**

6 OF 6

**SECTION 15: Regulatory Information**

**Chemical Inventories:** All components of this product listed in Section 2 are included on the TSCA inventory list, the DSL/NDSL and the EINECS

**Reportable Quantities (RQ):** None

**SARA TITLE III (Superfund Amendments and Reauthorization Act):**

**Section 302 Extremely Hazardous Materials:** None

**Section 304 Notification of Accidental Release:** None

**Sections 311/312 Hazard Categories:**

**Immediate (Acute) Health Effects:** YES

**Delayed (Chronic) Health Effects:** YES

**Fire Hazard:** NO

**Sudden Release of Pressure Hazard:** NO

**Reactivity Hazard:** NO

**Section 313 Toxic Chemical Release Reporting:** Not listed

**STATE REGULATORY INFORMATION:** Since each state has the authority to promulgate standards more stringent than the federal government, this section cannot provide an inclusive list of all state regulations that apply to this product. Questions related to state regulations should be directed toward local officials.

**STATUS UNDER CALIFORNIA PROPOSITION 65:** This product contains chemicals known to the state of California to cause cancer.

**SECTION 16: Other Information**

For additional information, refer to the 2000 Emergency Response Guidebook and the ACGIH Documentation of the Threshold Limit Values.

**This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of SPEC MIX®. The data on this sheet relates only to the specific material designated herein. SPEC MIX® assumes no legal responsibility for use or reliance upon this data.**