



SILO DELIVERY
SYSTEMS

G7000

ALL SEASON SILO ENCLOSURE SYSTEM



All Season Silo Mixing Station Made Easy!

The SPEC MIX® All Season Silo Enclosure System is a durable system developed to protect contractors working in cold, rainy, windy or sunny weather conditions. Custom designed to form fit the SPEC MIX G7000 silo system, this versatile silo enclosure consists of individual component pieces and panels to function as a total enclosure system for cold and rainy conditions or a partial system for wind and sun protection.

This portable and reusable weather barrier can be set up by one person in 20-minutes or less—all that is required is a step ladder. Made from durable marine-grade material, sturdy straps and metal clamps, the All Season Enclosure provides an excellent, economical solution to all-weather construction needs.

EASY INSTALLATION. FAST SET UP.
LIGHTWEIGHT. COLLAPSIBLE. FORM FITTED.
MULTIPLE ACCESS POINTS. ALL COMPONENTS
ARE REPLACEABLE. EXTENDED MIXING AREA.
INCREASES LABOR PRODUCTIVITY. STURDY,
ADJUSTABLE COMPONENTS.



G7000 ALL SEASON SILO ENCLOSURE SYSTEM



THE ALL SEASON SILO ENCLOSURE SYSTEM INCLUDES THE FOLLOWING:

- 1 Top Cover
- 2 Side Panels
- 1 Extension “Pop-Out” Panel
- 1 Door Panel
- 2 Steel Legs w/ Foot Pad for “Pop-Out”
- 2 Steel Truss Supports
- 1 Steel Double-Corner Cross Bar
- 1 Steel Center Truss Support
- 1 Tote Bag

SPECIFICATIONS

Material: Heavy Duty 10 oz. Marine Grade Polyester

Weight of cover: 40 lb (18.1 kg)

Weight of 1” steel framework: 40 lb (18.1 kg)

Total weight of silo enclosure: 80 lb (36.2 kg)

Dimension of silo enclosure extension/framework: 7 ft 6 in wide x 6 ft deep - 45 ft² (2.3 m x 1.8 m - 4.1 m²)

FOR MORE INFORMATION:

- CONTACT YOUR LOCAL SPEC MIX® MANUFACTURER
- VISIT WWW.SPECMIX.COM
- CONTACT SPEC MIX®, INC.
PHONE: 888-SPEC-MIX FAX: 651-454-5315

OPERATING AND SET UP INSTRUCTIONS



STEP 1: Begin by installing the top wrap around section first. Attach the top section while silo is in collapsed position. Wrap top panel around top of silo and hook straps to the 4 pick points. Attach bungee cords to grommets. . Make sure the ladder side is lined up with the ladder ensuring proper and secure fit. Adjust straps as necessary.



STEP 2: Raise Silo according to the SPEC MIX Silo Safety Manual. First, attach the 2 side panels before attaching the door panel. Wrap the 3 bungee straps of each side panels around the legs and attach to the grommets. Then attach the door panel to each side panel at 3 points using the strap & clamp system. Adjust straps so that the panels are a tight fit where appropriate. Note that each panel can be open and adjusted for extra ventilation.



STEP 3: The Pop-Out section of the silo enclosure provides extra room for the silo operator and any necessary mixing equipment such as water tanks, buckets, shovels and misc. tools. Attach the Pop-Out section of the silo enclosure by assembling the Pop-Out framework. First, connect the 2 legs to the Double Corner Cross Bar and pin. Next, connect the 2 Truss Supports to the Double Corner Cross Bar and pin. The end hooks of the Truss Supports must be inserted in the silo leg pocket. Last, connect the Center Truss Support to the silo and pin as well as the Double-Corner Cross Bar. Make sure the framework and pin points are secure.



STEP 4: Unfold the Pop-Out cover and pull it over and enclose the framework of the Pop-Out. Make adjustments to the inside of the Pop-Out cover to make sure it fits tight to each corner. Next, attach the Pop-Out panel to the side panels at 3 points using the strap & clamp system. Insert each leg foot pad into the corner pocket of the Pop-Out cover. Inside the Pop-Out cover is a bungee cord to secure the top of the Pop-Out cover to each leg of the framework. Make sure the flap on the top cover overhangs the Pop-Out section for proper water run-off.



STEP 5: The front of the silo enclosure lifts up and can be hooked to the top cover for easy operator and equipment access. A built-in pocket exists at the bottom of the door to hold a 2 in x 6 in (50.8 mm x 152.4 mm) wood board for added support.

IMPORTANT: End User is responsible for providing adequate ventilation consistent with normal construction enclosure. The SPEC MIX G7000 Silo Enclosure System is NOT flame retardant - Do not put in direct contact or close proximity with flame or heat source.